
SCHEPPER®

Linear Ceiling

www.schepper.in





Shaping Architectural Expression

Metal solutions for
contemporary spaces.

Founded in 2020, we set out to create architectural metal ceilings, façades, and elevation systems that don't just fill spaces but help define them.

Over the years, we have continued to improve. Better manufacturing. Stronger processes. Continuous R&D. Smarter solutions. Because architecture keeps evolving, and so should we.

Today, with an established presence and projects across India, we work closely with architects, interior designers, consultants, developers, contractors and channel partners to turn design intent into built reality.

Some see ceilings and façades as products.
We see them as part of the architecture.

What We Do

We create architectural metal ceilings, façades, and elevation systems that bring together design, engineering, and execution.

Solutions designed to perform. Spaces designed to be remembered.

Designed to grow beyond.

With a strong presence across key markets in India, we bring our expertise closer to every project we support.

What SCHEPPER. Stands For

Built on conviction,
Guided by purpose.

Vision

To shape the future of architectural systems through precision engineering, continuous innovation, uncompromising quality and enduring values. To become India's most trusted metal ceiling manufacturer, recognised for engineering-led design and responsible business practices, while enhancing the spaces where people live and work and setting new standards along the way.

Mission

We engineer architectural solutions in India, delivering world-class quality through advanced processes, continuous improvement and a commitment to international standards. Guided by quality, integrity and trust, we manufacture architectural solutions that support design excellence, build lasting relationships and deliver value to our customers, partners and people.

Our Core Principles



Innovation

Advancing architectural systems through forward-thinking engineering, emerging technologies and ideas that continually move our products forward.



Quality

Manufacturing to exacting standards, with the precision and performance our customers can rely on.



Customer Commitment

Listening closely to each project's needs so we can offer dependable solutions and service our customers can trust.



Integrity

Earning trust through honesty, transparency and ethical business practices. These are the foundations of lasting relationships.



Excellence

Striving to improve every day through our people, our processes and our manufacturing practices.



Growth

Treating every challenge as an opportunity to develop, adapt and create long-term value.

Progress, by Design

Built for what's next.

2020

Where It Began

Every organisation begins with a foundation. Ours was established in August 2020 by four founding members, united by a commitment to honesty, hard work and quality, and a clear focus on delivering architectural systems built on trust and reliability.

Our first year saw the introduction of the C Profile with an 8 mm groove and the Multi-C Profile concept, bringing greater flexibility and a clean, contemporary aesthetic to ceiling design.

2021

Building Momentum

As the quality of our work opened up new opportunities, our team and operations grew accordingly. We moved into a larger space, welcomed new talent and strengthened the capabilities needed to support our expanding market presence.

We also introduced customised G-Angle and J-Angle solutions for edge applications, along with a U-shaped baffle with a concealed groove for a refined, seamless finish.

2022

Expanding Our Reach

Growing market demand and encouragement from our clients led us to expand into southern India. The opportunity came sooner than expected, and we established a regional presence to serve the market more effectively and build a stronger foundation for future growth.

The year also saw the introduction of the REGAVOX Baffle and a fixed-rafter system in C Profile, expanding the possibilities for ceiling design.

2023

A Defining Milestone

2023 marked a significant milestone in our development. We expanded our capabilities to support the next stage of growth.

Later that year, we inaugurated our Hyderabad regional office and strengthened our local presence with a team from the region. This enabled closer communication and more responsive support for our customers. This growth was made possible by the continued encouragement of our clients and partners, whose trust helped shape our expansion across southern India. We remain committed to earning that trust through quality products and dependable service.

Strengthening Our Presence

In 2024, enhanced manufacturing capabilities supported further operational growth. With numerous dealers across India, our reach expanded alongside our project capabilities, allowing us to serve a wider range of markets and customers.

During the year, we successfully delivered projects across diverse sectors, strengthening our position as a trusted metal ceiling brand. The launch of our northern region division further expanded our reach, bringing us closer to our clients and enabling us to serve projects across India more efficiently.

2024

2025

Advancing with Confidence

In 2025, we expanded our manufacturing capabilities with a state-of-the-art facility equipped with advanced machinery, increasing production capacity, improving operational efficiency and supporting future growth.

The year also saw us obtain additional quality certifications aligned with global quality standards. We further strengthened our quality-control capabilities with an in-house laboratory and expanded our infrastructure with a dedicated stockholding facility, supporting our ability to deliver consistent quality at scale.

2026

The Journey Continues

Our progress has been shaped by the trust of our clients, the experience gained through every challenge, and the relationships built along the way. These continue to guide how we work and how we approach what comes next.

As we move forward, our focus remains on strengthening our capabilities, advancing our solutions and creating lasting value while staying true to the principles that have shaped us from the beginning.

Designed to be chosen.

From concept development
to site execution.



Performance Built In

Engineered to deliver durability, safety and long-term reliability.



Detail Driven

From finishes to installation, precision is never an afterthought.



Ready for Real-World Conditions

Built to perform across diverse real-world environments and project requirements.



Design Meets Execution

A seamless balance between architectural intent and practical application.



Responsive Partnership

Clear communication, technical support and dependable project coordination.



Consistency You Can Trust

The same commitment to quality across every project, every time.



Designed Around Your Vision

Customisations that adapt to your design, not the other way around.

Form. Function. Finish.

Three essentials.
One integrated approach.

We believe the relationship between design, engineering and execution defines how architectural spaces take shape.


From ceilings and façades to the finer details of an interior, every element contributes to the character and performance of a space. Our focus extends beyond individual products to developing architectural systems that complement the broader design intent.

Our solutions combine considered design, practical engineering and quality manufacturing, giving architects, designers and project teams the flexibility to realise a wide range of applications.

By bringing design intent and technical capability together, we create architectural systems that help shape spaces that are functional, refined and built to last.









Architectural Systems Across Industries

Solutions designed for the demands of every space.

Our architectural ceiling systems are designed to meet the functional, aesthetic and performance requirements of diverse built environments. From large-scale infrastructure projects to commercial and institutional spaces, we work with architects, interior designers, consultants, project teams and channel partners to deliver solutions tailored to each application.









Where We Work

Airports

Metro and Rail

Commercial Offices

Retail and Shopping Centres

Malls

Hospitality

Residential Projects

Hospitals

Educational Institutions

Industrial and Infrastructure Projects

And many more

Performance, verified independently.


Validated against globally recognised standards.

Schepper develops and evaluates its metal ceiling systems in accordance with applicable internationally recognised standards for fire safety, acoustics, durability, surface finishes, indoor air quality and system performance.

An Indian metal ceiling manufacturer delivering performance aligned with Internationally recognized standards for suspended ceiling systems, with a strong emphasis on Indian sourcing.







System Compliance

EN 13964:2014

Suspended Ceiling Systems:
Requirements and Test Methods

Performance Evaluation	Applicable Test Standard / Method
Suspended Ceiling Requirements and Test Methods	Tested in accordance with EN 13964:2014
Reaction to Fire Classification	EN 13501-1:2018 – A2-s1,d0
Flame Spread and Smoke Developed Index	ASTM E84
Sound Absorption	ISO 354:2003
Sound Absorption Rating	ISO 11654:1997
Sound Absorption (NRC)	IS 8225:2018
Antibacterial Activity	ISO 22196:2011
Dry Film Thickness	ISO 2808:2019
Gloss	ISO 2813:2014
Cross-Cut Adhesion	ISO 2409:2020
Salt Spray Corrosion Resistance	ISO 9227:2022
Total Volatile Organic Compounds (TVOC)	ISO 16000-6:2021 / EN 16516:2017+A1:2020
Formaldehyde Emission	IS 17118 (Part 3):2022 / ISO 16000-3:2011

Certifications & Compliance

Documented performance against applicable International and Indian requirements.

Coating Quality and Performance

- QUALICOAT - Class 2-3 (Approved Coater)
- AAMA 2603–2605 - Applicable Coating Performance Specifications

Environmental and Organisational Certifications

- GreenPro - Environmental Product Certification, where applicable
- ZED Gold - Zero Defect Zero Effect Certification
- ISO 9001:2015 - Quality Management System
- ISO 14001:2015 - Environmental Management System
- ISO 45001:2018 - Occupational Health and Safety Management System

Our Commitment

- At Schepper, quality is supported by systematic process control, relevant testing methods and a commitment to dependable architectural ceiling solutions.

Performance Test Disclaimer

- All stated performance tests have been conducted on lay-in tile and baffle ceiling systems in their standard installation configurations, using standard product patterns, suspension components and recommended installation methods.
- Testing was carried out by NABL-accredited laboratories.
- Performance may vary depending on material, thickness, perforation, coating, acoustic properties, on-site suspension arrangements and system configuration.
- Independent laboratory test reports and supporting compliance documents can be provided for consultant review upon request.

Sustainability by Design

Responsible Materials. Responsible Manufacturing.

Sustainability at Schepper extends across the manufacturing lifecycle, from responsible material sourcing and efficient production to refurbishment, waste management, energy use and end-of-life considerations. Our approach focuses on reducing environmental impact whilst maintaining the quality and performance of our architectural systems.

Our commitment is supported by GreenPro Certification and ZED Gold Certification, reflecting our focus on sustainable manufacturing, consistent product quality and responsible environmental practices.

Responsible Sourcing

We select materials and finishes with consideration for performance, durability and responsible manufacturing.

- Aluminium and Aluminium Alloys (3000, 6000 and 8000 series): Selected for architectural performance and durability.
- Galvanised Steel (Zinc Coating Z80 - Z120, IS 277): Selected for strength, corrosion resistance and long-term performance.
- Architectural Coatings: Applied to provide durable surface protection and a consistent finish.

Recognised Sustainability Credentials


GreenPro Certified

- Recognised for meeting established sustainability criteria for products used in the built environment.

ZED Gold Certified

- The Government of India's Zero Defect Zero Effect initiative recognises manufacturing practices focused on quality, efficiency and reduced environmental impact.

Across the Manufacturing Lifecycle



Engineered in Metal

Material, Process and Precision

The performance of an architectural system depends on more than its design. The materials, manufacturing processes and attention to detail behind it are equally important. At Schepper, we bring these elements together through carefully selected materials, controlled manufacturing processes and consistent quality checks.

We manufacture our metal ceiling systems using aluminium alloys and galvanised steel coil, combining material performance with the flexibility required for contemporary architectural applications. From surface preparation and powder coating to curing, inspection and dispatch, every stage is carefully controlled to deliver consistent quality and finish.



Why Metal?

Metal provides the strength, durability and design flexibility required across a wide range of architectural applications.

- **Durable -** Built to deliver consistent performance over time.
- **Flexible -** Adaptable to different profiles, forms, finishes and applications.
- **Stable -** Offers consistent dimensional accuracy and surface quality.
- **Practical -** Supports installation, access and maintenance requirements.
- **Recyclable -** Aluminium and galvanised steel can be recovered and recycled.

A Controlled Manufacturing Process

Every Schepper metal ceiling passes through a defined production flow:

Design

Each project is detailed in-house. Layouts, panel and tile sizes, perforation, and suspension systems are engineered to approved drawings before production begins.

Forming

Coils are cut, punched, and formed using roll-forming lines, CNC press brakes, and fibre laser equipment to achieve the specified profiles and tolerances.

Dimensional QC

Formed components are checked for length, width, flatness, and profile at defined intervals throughout each production run to ensure dimensional accuracy and consistency.

Pre-treatment

Multi-stage chemical conversion prepares the metal surface for coating. Suitable alternative processes may be used where required.



Final Rinse

Demineralised water is preferred for the final rinse to help minimise surface residue before coating.

Powder Coating

Architectural-grade powder is applied using electrostatic spray coating to achieve a consistent colour and finish.

Cooling & Inspection

Coated components are cooled and inspected to assess finish quality and consistency.

Drying

Components are thoroughly dried to ensure they are free from moisture before powder coating.

Curing

The coating is cured in accordance with the powder manufacturer's technical data sheet (TDS), with curing conditions determined by the metal temperature.

QC & Dispatch

Final quality checks are completed before dispatch.

Safety in Manufacturing

Safety and environmental responsibility are integral to our manufacturing processes. Defined procedures, controlled operations and appropriate safety measures help protect our people while maintaining a disciplined production environment. Our commitment is supported by the ISO 14001:2015 Environmental Management System and ISO 45001:2018 Occupational Health and Safety Management System standards.

From Material to System

Our manufacturing approach is built around control at every stage. By combining the right materials with a disciplined production process, we create metal ceiling systems that deliver consistent quality, dependable performance and lasting value.

SCHEPPER®



Index

01 Linear Ceiling

- Strova 17
- Krosavar 19
- Arqen 21
- Planum 23
- Fluven 25
- Univex 27
- Rithmex 29
- Krestova 31
- Seamra 33
- Rondex 35

02 Colour, Shade and Finish Options 37

03 Perforation, Patterns and Specifications 39

04 Acoustic Ceiling Solutions 49

05 Suspension Details 50


Strova



Some ceilings are designed to complete a space. Others help define it. Strova belongs to the latter, a linear ceiling system that brings rhythm, proportion, and material precision to the overhead plane, combining the warmth of timber with the permanence of engineered metal.

Engineered as Schepper's C Profile linear ceiling system, Strova features precision-formed tongue-and-groove panels that snap onto a concealed carrier to create a continuous ceiling with crisp shadow lines and a strong directional character. With multiple panel widths and multiple groove configurations, it offers architects exceptional design flexibility across corporate, hospitality, retail, transit, and cultural environments.

Patterns in Strova



Multiple patterns can be customised

Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

- Acoustic Property — NRC - Up to 0.95*
- Fire Classification — EN 13501-1 A2-s1,d0* ASTM E84 Tested*
- Corrosion Resistance — Salt Spray Resistance*: 1,000 h GS • 1,500 h Aluminium
- Antimicrobial Performance*
- VOC Emissions: Below Detection Limit*
- Long-term Durability

- Design Flexibility
- Humidity Resistance
- Up to 95% Recyclable by Mass*
- Easy to Clean
- Sustainable Building Material
- Light Reflectance
- Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	-
7	Panel Coupler	-	-
8	Carrier Coupler	-	-

Panel Specification

Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	38	5000	15	0.65 - 1.20	0.50 - 0.71
6.2	60	5000	15	0.65 - 1.20	0.50 - 0.71
6.3	84	5000	15	0.65 - 1.20	0.50 - 0.71
6.4	92	5000	15	0.65 - 1.20	0.50 - 0.71
6.5	128	5000	15	0.65 - 1.20	0.50 - 0.71
6.6	136	5000	15	0.65 - 1.20	0.50 - 0.71
6.7	146	5000	15	0.65 - 1.20	0.50 - 0.71
6.8	184	5000	15	0.65 - 1.20	0.50 - 0.71
6.9	196	5000	15	0.65 - 1.20	0.50 - 0.71
6.10	212	5000	15	0.65 - 1.20	0.50 - 0.71
6.11	284	5000	15	0.65 - 1.20	0.50 - 0.71


*Panel can be customised

Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)


Periphery Specification

Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P1	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
P2	"C" Angle	40x50x18	2440	0.65 - 1.20	0.50 - 0.71
P3	"J" Angle	50x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
P4	"G" Angle	40x60x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-


*Periphery can be customised




Installation Options



Strova 1



Strova 2




Strova 3


System Weight per m²
6.5 kg/m² (Estimated)
as per "Strova 2"

Strova (C Profile) system incorporating 84C GS 0.50 mm panels with 16 mm uniform spacing, complete with Strova 2 accessories, set for a 500 mm suspended installation.


Periphery Options




Edge Profile



C-Angle




J-Angle



G-Angle

Note - all measurements are in mm.


Krosavar®



Some spaces demand more than a ceiling; they demand a structure that can keep pace with architectural ambition. Krosavar is conceived for these moments, extending the language of linear planking across larger spans while introducing a greater sense of depth, scale, and structural expression to the overhead plane.

Developed as Schepper's C Profile Rafter linear ceiling system, Krosavar features precision-formed tongue-and-groove panels supported by an aluminium box-rafter sub-frame, creating a continuous ceiling with crisp shadow lines and enhanced spanning capability. Sharing the same panel vocabulary as Strova, it offers architects the flexibility to achieve consistent linear compositions across projects with varying structural and suspension requirements.

Patterns in Krosavar



Multiple patterns can be customised

Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

Acoustic Property
NRC - Up to 0.95*

Fire Classification
EN 13501-1 A2-s1,d0*
ASTM E84 Tested*

Corrosion Resistance
Salt Spray Resistance*:
1,000 h GS • 1,500 h Aluminium

Antimicrobial Performance*

VOC Emissions:
Below Detection Limit*

Long-term Durability

Design Flexibility

Humidity Resistance

Up to 95% Recyclable by Mass*

Easy to Clean

Sustainable Building Material

Light Reflectance

Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	-
7	Panel Coupler	-	-
8	Carrier Coupler	-	-
9	Rafter	-	-

Panel Specification

Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	38	5000	15	0.65 - 1.20	0.50 - 0.71
6.2	60	5000	15	0.65 - 1.20	0.50 - 0.71
6.3	84	5000	15	0.65 - 1.20	0.50 - 0.71
6.4	92	5000	15	0.65 - 1.20	0.50 - 0.71
6.5	128	5000	15	0.65 - 1.20	0.50 - 0.71
6.6	136	5000	15	0.65 - 1.20	0.50 - 0.71
6.7	146	5000	15	0.65 - 1.20	0.50 - 0.71
6.8	184	5000	15	0.65 - 1.20	0.50 - 0.71
6.9	196	5000	15	0.65 - 1.20	0.50 - 0.71
6.10	212	5000	15	0.65 - 1.20	0.50 - 0.71
6.11	284	5000	15	0.65 - 1.20	0.50 - 0.71

*Panel can be customised

Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)

Rafter Specification


Code	Component	Size (Inch)	Length (Up to)	Aluminium Thickness (mm)
9.1	Box Rafter	1"x3"	3600	1.20 - 2.00
9.2	Box Rafter	1"x4"	3600	1.20 - 2.00
9.3	Box Rafter	1"x5"	3600	1.20 - 2.00
9.4	Box Rafter	2"x3"	3600	1.20 - 2.00
9.5	Box Rafter	2"x4"	3600	1.20 - 2.00
9.6	Box Rafter	2"x5"	3600	1.20 - 2.00

All box rafter sizes are specified in inches.


Periphery Specification

Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P1	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
P2	"C" Angle	40x50x18	2440	0.65 - 1.20	0.50 - 0.71
P3	"J" Angle	50x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
P4	"G" Angle	40x60x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-

*Periphery can be customised




Installation Options



Krosavar 1 | Krosavar 2 | Krosavar 3

Rafter Fixing




Rafter Fixing | Rafter Fixing

System Weight per m²
8.00 kg/m² (Estimated)
as per "Krosavar 2"

Krosavar (C Profile with Rafter) system incorporating 84C GS 0.50 mm panels with 16 mm uniform spacing, complete with Krosavar 2 accessories, set for a 500 mm suspended installation (with 1.2 mm thick 1"x4" rafter).

Periphery Options



Edge Profile | C-Angle | J-Angle | G-Angle

Note - all measurements are in mm.*


Arqen



Not every architectural surface needs to command attention. Some perform their role through proportion, rhythm, and the way they hold light across a space. Arqen is conceived around this idea: a linear ceiling that softens the precision of metal with a subtle radiused profile, bringing warmth and continuity to the overhead plane.

Envisioned as Schepper's R Profile linear ceiling system, Arqen features precision-formed panels that interlock with a concealed carrier and are securely fixed in place, creating a semi-closed ceiling with defined reveal gaps and a strong directional grain. Multiple panel widths can be composed into architect-specified patterns, offering a balance of architectural expression, demountable functionality, and enduring material performance across premium workplaces, hospitality, retail, transit, and healthcare interiors.

Patterns in Arqen



Multiple patterns can be customised

Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

- Acoustic Property — NRC - Up to 0.95*
- Fire Classification — EN 13501-1 A2-s1,d0* ASTM E84 Tested*
- Corrosion Resistance — Salt Spray Resistance*: 1,000 h GS • 1,500 h Aluminium
- Antimicrobial Performance*
- VOC Emissions: Below Detection Limit*
- Long-term Durability

- Design Flexibility
- Humidity Resistance
- Up to 95% Recyclable by Mass*
- Easy to Clean
- Sustainable Building Material
- Light Reflectance
- Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	
7	Panel Coupler	-	-
8	Carrier Coupler	-	-
9	Flush Cap	16x15	Up to 2440

Panel Specification

Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	38	5000	15	0.65 - 1.20	0.50 - 0.71
6.2	60	5000	15	0.65 - 1.20	0.50 - 0.71
6.3	84	5000	15	0.65 - 1.20	0.50 - 0.71
6.4	136	5000	15	0.65 - 1.20	0.50 - 0.71
6.5	184	5000	15	0.65 - 1.20	0.50 - 0.71
6.6	212	5000	15	0.65 - 1.20	0.50 - 0.71
6.7	284	5000	15	0.65 - 1.20	0.50 - 0.71


*Panel can be customised
Note: Arqen is subject to wind load.

Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)


Periphery Specification

Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P1	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
P2	"C" Angle	40x50x18	2440	0.65 - 1.20	0.50 - 0.71
P3	"J" Angle	50x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
P4	"G" Angle	40x60x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-


*Periphery can be customised




Installation Options



Arqen 1



Arqen 2




Arqen 3


System Weight per m²
5.40 kg/m² (Estimated)
as per "Arqen 2"

Arqen (R Profile) system incorporating 84R GS 0.50 mm panels with 16 mm uniform spacing, complete with Arqen 2 accessories, set for a 500 mm suspended installation.


Periphery Options




Edge Profile



C-Angle



J-Angle



G-Angle

Note - all measurements are in mm.

Planum®



Some architectural surfaces find their strength in consistency. Planum embraces this principle through a disciplined linear plane, where a single panel width creates a calm, continuous rhythm across the ceiling. Its clean geometry and restrained detailing allow the surface to complement the architecture without overpowering it, creating an overhead expression that feels precise, composed and enduring.

Envisioned as Schepper's F Profile linear ceiling system, Planum features precision-formed 150 mm panels that interlock with a concealed carrier and are securely fixed in place, creating a clean, near-continuous metal plane. Designed for ceilings,and soffits applications, its long-format panels and simple clip-in construction offer architects greater freedom in creating uninterrupted linear surfaces, while maintaining the accessibility, flexibility, and engineered performance expected from a modular metal system.

Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

Acoustic Property
NRC - Up to 0.95*

Fire Classification
EN 13501-1 A2-s1,d0*
ASTM E84 Tested*

Corrosion Resistance
Salt Spray Resistance*:
1,000 h GS • 1,500 h Aluminium

Antimicrobial Performance*

VOC Emissions:
Below Detection Limit*

Long-term Durability

Design Flexibility

Humidity Resistance

Up to 95% Recyclable by Mass*

Easy to Clean


Sustainable Building Material

Light Reflectance

Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
D1	Anchor Fastener	Ø 6/8	50
D2	Suspension Angle (0.50 mm)	-	-
D3	T Leveller (1.20 mm)	-	-
D4	M6/8x10 Nut & Bolt	Ø 6/8	10
D5	Self-Drilling Screw	-	-
6	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	45x20x45	Up to 2440
7	Panel	-	-
8	Panel Coupler	-	-
9	Carrier Coupler	-	-




Panel Specification


Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
7	150	6000	15	0.65 - 1.20	0.50 - 0.71

Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)


Installation Options




Planum 1



Planum 2



Planum 3



Planum 4

Periphery Specification


Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P1	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
P2	"C" Angle	40x50x18	2440	0.65 - 1.20	0.50 - 0.71
P3	"J" Angle	50x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
P4	"G" Angle	40x60x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-

*Periphery can be customised


System Weight per m²
6.07 kg/m² (Estimated)
as per "Planum 2"

Planum (F Profile) system incorporating 150F GS 0.50 mm panels, complete with Planum 2 accessories, set for a 500 mm suspended installation.


Periphery Options




Edge Profile



C-Angle




J-Angle



G-Angle

Note - all measurements are in mm.


Fluven®



The most enduring architectural surfaces are often the simplest—calm, uninterrupted, and resolved with confidence. Fluven is designed to create that sense of visual stillness, transforming individual panels into a singular ceiling plane that feels effortless in both composition and execution.

Engineered as Schepper's S Profile linear ceiling system, Fluven features wide-format panels with concealed junctions that form a fully closed, monolithic soffit. Its broad proportions and clean shadow lines allow architects to create expansive overhead surfaces with the durability and engineering precision of metal across hospitality, corporate, cultural, and premium retail environments.

Patterns in Fluven



Multiple patterns can be customised


Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

- Acoustic Property — NRC - Up to 0.95*
- Fire Classification — EN 13501-1 A2-s1,d0* ASTM E84 Tested*
- Corrosion Resistance — Salt Spray Resistance*: 1,000 h GS • 1,500 h Aluminium
- Antimicrobial Performance*
- VOC Emissions: Below Detection Limit*
- Long-term Durability

- Design Flexibility
- Humidity Resistance
- Up to 95% Recyclable by Mass*
- Easy to Clean
- Sustainable Building Material
- Light Reflectance
- Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	-
7	Panel Coupler	-	-
8	Carrier Coupler	-	-




Panel Specification


Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	75	5000	15	0.65	0.50
6.2	150	5000	15	0.65	0.50
6.3	225	5000	15	0.65	0.50
6.4	300	5000	15	0.65	0.50

Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)


Installation Options



Fluven 1



Fluven 2



Fluven 3

Periphery Specification


Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P1	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
P2	"C" Angle	40x50x18	2440	0.65 - 1.20	0.50 - 0.71
P3	"J" Angle	50x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
P4	"G" Angle	40x60x18x12x5	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-

*Periphery can be customised


System Weight per m²
7.00 kg/m² (Estimated)
as per "Fluven 2"

Fluven (S Profile) system incorporating 75S GS 0.50 mm panels, complete with Fluven 2 accessories, set for a 500 mm suspended installation.


Periphery Options




Edge Profile



C-Angle



J-Angle



G-Angle

Note - all measurements are in mm.

Univex



A ceiling does not always need to form a continuous plane. Sometimes, its character comes from the rhythm between what is present and what is left open. Univex embraces this idea through a disciplined field of vertical fins, creating a sense of depth, movement, and openness while allowing the structure and services above to remain part of the spatial expression.

Developed as Schepper's U Profile baffle ceiling system, Univex features precision-formed metal fins that clip onto a concealed carrier to create a clean, rhythmic open ceiling. With a consistent profile across the field, it brings visual order, and easy access to the plenum, making it well suited to workplaces, hospitality environments, transit spaces, retail interiors, and other projects where openness is an essential part of the architecture.


Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

- Acoustic Property
  NRC - Up to 0.95*
- Fire Classification
  EN 13501-1 A2-s1,d0*
  ASTM E84 Tested*
- Corrosion Resistance
  Salt Spray Resistance*:
  1,000 h GS • 1,500 h Aluminium
- Antimicrobial Performance*
- VOC Emissions:
  Below Detection Limit*
- Long-term Durability

- Design Flexibility
- Humidity Resistance
- Up to 95% Recyclable by Mass*
- Easy to Clean
- Sustainable Building Material
- Light Reflectance
- Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	-
7	Panel Coupler	-	-
8	Carrier Coupler	-	-
9	End Cap	-	-




Panel Specification

Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	50 | 75 | 100 | 125 | 150	5000	13	0.65 - 1.20	0.50 - 0.71
6.2	25 | 50 | 75 | 100 | 125	5000	25	0.65 - 1.20	0.50 - 0.71
6.3	25 | 50 | 75 | 100 | 125	5000	50	0.65 - 1.20	0.50 - 0.71
6.4	25 | 50 | 75 | 100 | 125	5000	75	0.65 - 1.20	0.50 - 0.71
6.5	25 | 50 | 75 | 100 | 125	5000	100	0.65 - 1.20	0.50 - 0.71
6.6	25 | 50 | 75 | 100 | 125	5000	125	0.65 - 1.20	0.50 - 0.71
6.7	25 | 50 | 75	5000	150	0.65 - 1.20	0.50 - 0.71


*Panel can be customised

Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)


Installation Options



Univex 1



Univex 2




Univex 3

Periphery Specification

Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-

*Periphery can be customised

Periphery Option



Edge Profile

System Weight per m²
7.80 kg/m² (Estimated)
as per "Univex 2"

Univex (U Shape Flat) system incorporating 25x25x25 GS 0.50 mm panels with 25 mm uniform spacing, complete with Univex 2 accessories, set for a 500 mm suspended installation.

Note - all measurements are in mm.


Rithmex®



Architecture is often defined by the lines we choose to repeat. Rithmex builds upon this idea, transforming the ceiling into a composition of rhythm, movement, and visual cadence. By combining varying baffle widths in deliberate sequences, it creates an overhead plane that changes subtly with perspective, bringing depth and dynamism to the spaces below.

Engineered as Schepper's multi-width U Profile baffle ceiling system, Rithmex features precision-formed metal fins clipped onto a concealed carrier to create architect-specified patterns with a strong directional character. Sharing a common platform with the wider Schepper baffle family, it offers exceptional compositional flexibility across airports, hospitality spaces, corporate interiors, cultural institutions, and premium retail environments.

Patterns in Rithmex



Multiple patterns can be customised


Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

- Acoustic Property — NRC - Up to 0.95*
- Fire Classification — EN 13501-1 A2-s1,d0* ASTM E84 Tested*
- Corrosion Resistance — Salt Spray Resistance*: 1,000 h GS • 1,500 h Aluminium
- Antimicrobial Performance*
- VOC Emissions: Below Detection Limit*
- Long-term Durability

- Design Flexibility
- Humidity Resistance
- Up to 95% Recyclable by Mass*
- Easy to Clean
- Sustainable Building Material
- Light Reflectance
- Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	-
7	Panel Coupler	-	-
8	Carrier Coupler	-	-
9	End Cap	-	-



Panel Specification

Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	50 I 75 I 100 I 125 I 150	5000	13	0.65 - 1.20	0.50 - 0.71
6.2	25 I 50 I 75 I 100 I 125	5000	25	0.65 - 1.20	0.50 - 0.71
6.3	25 I 50 I 75 I 100 I 125	5000	50	0.65 - 1.20	0.50 - 0.71
6.4	25 I 50 I 75 I 100 I 125	5000	75	0.65 - 1.20	0.50 - 0.71
6.5	25 I 50 I 75 I 100 I 125	5000	100	0.65 - 1.20	0.50 - 0.71
6.6	25 I 50 I 75 I 100 I 125	5000	125	0.65 - 1.20	0.50 - 0.71
6.7	25 I 50 I 75	5000	150	0.65 - 1.20	0.50 - 0.71

*Panel can be customised


Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)

Periphery Specification


Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-

*Periphery can be customised


Installation Options



Rithmex 1




Rithmex 2



Rithmex 3

Periphery Option



Edge Profile

System Weight per m²
7.11 kg/m² (Estimated)
as per "Rithmex 2"

Rithmex (U Shape Multi Width) system incorporating GS 0.50 mm panels with 25mm height and variable width patterns (25-25-50-25-25-50 mm) with 25 mm uniform spacing, complete with Rithmex 2 accessories, set for a 500 mm suspended installation.

Note - all measurements are in mm.

Krestova

Some ceilings define a plane. Others create a landscape. Krestova is designed to introduce depth, transforming the overhead surface into a sculpted composition of light, shadow, and movement. Through varying baffle heights, it brings a distinct three-dimensional character to a space, creating an architectural experience that changes with every perspective.

Envisioned as Schepper's multi-depth U Profile baffle ceiling system, Krestova features precision-formed metal fins suspended from a shared carrier to create layered ceiling compositions with remarkable visual depth. With multiple depth combinations, it offers architects exceptional freedom to shape expressive overhead environments across airports, hospitality spaces, corporate atria, retail interiors, and cultural destinations.

Patterns in Krestova



25D-25 | 50D-25 | 50D-25 | 50D-25 | 25D-25



50D-25 | 75D-25 | 75D-25 | 50D-25



50D-25 | 75D-25 | 100D-25 | 75D-25 | 50D-25



100D-25 | 25D-25 | 50D-25 | 25D-25 | 50D-25 | 25D-25 | 100D-25

Multiple patterns can be customised

Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

- Acoustic Property — NRC - Up to 0.95*
- Fire Classification — EN 13501-1 A2-s1,d0* ASTM E84 Tested*
- Corrosion Resistance — Salt Spray Resistance*: 1,000 h GS • 1,500 h Aluminium
- Antimicrobial Performance*
- VOC Emissions: Below Detection Limit*
- Long-term Durability
- Design Flexibility
- Humidity Resistance
- Up to 95% Recyclable by Mass*
- Easy to Clean
- Sustainable Building Material
- Light Reflectance
- Demountable and Easy to Maintain

Assembly & Component ID


Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	-
7	Panel Coupler	-	-
8	Carrier Coupler	-	-
9	End Cap	-	-

Panel Specification


Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	50 I 75 I 100 I 125 I 150	5000	13	0.65 - 1.20	0.50 - 0.71
6.2	25 I 50 I 75 I 100 I 125	5000	25	0.65 - 1.20	0.50 - 0.71
6.3	25 I 50 I 75 I 100 I 125	5000	50	0.65 - 1.20	0.50 - 0.71
6.4	25 I 50 I 75 I 100 I 125	5000	75	0.65 - 1.20	0.50 - 0.71
6.5	25 I 50 I 75 I 100 I 125	5000	100	0.65 - 1.20	0.50 - 0.71
6.6	25 I 50 I 75 I 100 I 125	5000	125	0.65 - 1.20	0.50 - 0.71
6.7	25 I 50 I 75	5000	150	0.65 - 1.20	0.50 - 0.71

*Panel can be customised


Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)




Installation Options



Krestova 1



Krestova 2




Krestova 3

System Weight per m²
9.42 kg/m² (Estimated)
as per "Krestova 2"

Krestova (U Shape Multi Depth) system incorporating GS 0.50 mm panels with 25 mm width and variable depth patterns (25-50-50-25-25-50-50 mm) with 25 mm uniform spacing, complete with Krestova 2 accessories, set for a 500 mm suspended installation.


Note - all measurements are in mm.

Seamra®



The most refined ceilings are often defined by what they choose not to reveal. Seamra is designed around this principle, creating a disciplined field of vertical fins where fixings and engagement details disappear entirely from view. The result is a clean, uninterrupted rhythm of metal blades that gives the ceiling a sense of precision and restraint, allowing the architecture beneath it to remain the focus.

Developed as Schepper's concealed engagement baffle ceiling system, Seamra features precision-formed U profile fins that lock into a recessed groove along the top flange, keeping the connection completely hidden from below. Fully demountable and built on Schepper's shared carrier system, it combines a monolithic visual expression with practical access to the plenum, making it ideal for premium workplaces, galleries, hospitality interiors, luxury retail, and other spaces where every architectural detail matters.



Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

Acoustic Property
NRC - Up to 0.95*

Fire Classification
EN 13501-1 A2-s1,d0*
ASTM E84 Tested*

Corrosion Resistance
Salt Spray Resistance*:
1,000 h GS • 1,500 h Aluminium

Antimicrobial Performance*

VOC Emissions:
Below Detection Limit*

Long-term Durability

Design Flexibility

Humidity Resistance

Up to 95% Recyclable by Mass*

Easy to Clean


Sustainable Building Material

Light Reflectance

Demountable and Easy to Maintain

Assembly & Component ID

Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8x10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.60 mm) OR Alu. Carrier (0.90 mm)	40x20x40	Up to 4000
6	Panel	-	-
7	Panel Coupler	-	-
8	Carrier Coupler	-	-
9	End Cap	-	-




Panel Specification

Code	Width	Length (Up to)	Depth	Aluminium Thickness	Galvanised Steel Thickness
6.1	25	5000	25	0.65 - 1.20	0.50 - 0.71
6.2	50	5000	25	0.65 - 1.20	0.50 - 0.71
6.3	75	5000	25	0.65 - 1.20	0.50 - 0.71
6.4	100	5000	25	0.65 - 1.20	0.50 - 0.71
6.5	125	5000	25	0.65 - 1.20	0.50 - 0.71


*Panel can be customised

Metal: A. Galvanised Steel (Z80 / Z120)
B. Aluminium Alloys (3000, 6000, 8000 Series)


Installation Options



Seamra 1



Seamra 2




Seamra 3

Periphery Specification

Code	Component	Size	Length (Up to)	Aluminium Thickness	Galvanised Steel Thickness
P	Edge Profile	20x18	2440	0.65 - 1.20	0.50 - 0.71
N	Wall Plug & SS Screw	Plug: 8x50 & Screw: 8x50	-	-	-

*Periphery can be customised

Periphery



Edge Profile

System Weight per m²
9.99 kg/m² (Estimated)
as per "Seamra 2"

Seamra (Concealed U Shape) system incorporating 25x25x25 GS 0.50 mm panels with a 25 mm flange on one side and 25 mm uniform spacing, complete with Seamra 2 accessories, set for a 500 mm suspended installation.

Note - all measurements are in mm.

Rondex®



Not every linear ceiling needs to feel rigid. Rondex brings a softer expression to the open ceiling through the simple geometry of the circle, allowing light to move gently across its curved surfaces while maintaining a strong directional rhythm. The result is an open, layered ceiling that gives the space depth without closing off the volume above, keeping services, structure, and light integrated into the architectural composition.

Engineered as Schepper's tube baffle ceiling system, Rondex features precision-formed cylindrical aluminium tubes suspended from a concealed carrier to create a clean, continuous rhythm across the ceiling plane. Available in two standard diameters and fully demountable for individual access, it combines visual softness with engineered precision, making it well suited to transit spaces, workplaces, hospitality environments, retail interiors, and large public spaces.

Note: Perforation is not available for this profile.

Designed and manufactured in accordance with internationally recognised standards for suspended ceiling quality, performance and testing.

- Acoustic Property
  NRC - Up to 0.95*
- Fire Classification
  EN 13501-1 A2-s1,d0*
  ASTM E84 Tested*
- Corrosion Resistance
  Salt Spray Resistance*:
  1,500 h Aluminium
- Antimicrobial Performance*
- VOC Emissions:
  Below Detection Limit*
- Long-term Durability

- Design Flexibility
- Humidity Resistance
- Up to 95% Recyclable by Mass*
- Easy to Clean
- Sustainable Building Material
- Light Reflectance
- Demountable and Easy to Maintain

Assembly & Component ID


Code	Component	Size	Length
A1	Bullet Fastener	Ø 6/8	25
A2	Threaded Rod	Ø 6/8	Up to 1800
A3	Carrier Support Angle	25x25x25	Up to 2440
A4	M6/8 x 10 Nut & Bolt	Ø 6/8	10
B1	Pop Anchor Fastener	Ø 6	25
B2	Galvanised Iron Rod	Ø 4	Up to 2440
B3	Height Adjustable Clip	-	-
C1	Bullet Fastener	Ø 6/8	25
C2	Threaded Rod	Ø 6/8	Up to 1800
5	GS Carrier (0.80 mm) OR Alu. Carrier (1.20 mm)	40x20x40	Up to 4000
6	Tube Baffle	-	-
7	Carrier Coupler	-	-
8	End Cap	Ø 60/85	-

Panel Specification


Code	Diameter	Length (Up to)	Aluminium Thickness
6.1	60	5000	0.70 - 1.50
6.2	85	5000	0.70 - 1.50

*Panel can be customised


Metal: Aluminium Alloys (3000, 6000, 8000 Series)




Installation Options



Rondex 1



Rondex 2



Rondex 3

System Weight per m²
9.8 kg/m² (Estimated)
as per "Rondex 2"

Rondex (Tube Baffle) system incorporating Aluminium 1.2mm tube panels with 60mm diameter and end caps on sides with 50 mm uniform spacing, complete with Rondex 2 accessories, set for a 500 mm suspended installation.

Note - all measurements are in mm.

Colour, Shade and Finish Options

Pre-Treatment Process of Powder Coating

During this process, metal ceiling panels pass through several stages, including degreasing, water rinsing, pickling or derusting, phosphating, final rinsing and passivation.

Each stage helps remove oil, dust, rust, oxide layers and chemical residues while creating a protective phosphate layer on the metal surface.

This process improves paint adhesion, corrosion resistance, coating durability and overall finish quality, ensuring that every metal ceiling panel delivers long-lasting performance with a clean, premium finish.

Scan the QR Code
for more details

Coating & Surface Finish

Schepper uses architectural-grade powder coatings, designed for durability, a consistent finish, and low environmental impact.

Quality Compliance

System Compliance
EN 13964:2014
Suspended Ceiling Systems

Powder Coating
Qualicoat Class 1-3
AAMA 2603 / 2605
EN 12206:2021



Colour Specifications

RAL is a standardised colour-matching system used to specify and coordinate colours across architectural metal applications, including ceilings, façades and elevation systems.

Solid colours can be customised from a range of standard shades, offering flexibility in design.

Wooden and textured finishes are available in a curated range of options, bringing depth, character and refinement to architectural spaces.

Actual colour appearance may vary depending on the coating, surface texture, gloss level and lighting conditions.

Wooden Finish


S621008


S621002


S121017


S121023


S421016


S421011


S621003


S621004


S121016


S421021


S221009


S421004

Texture Finish


S712508


S712505


S712503


S412504



S411523


S411520


S411501


S411507


S712502


S712519


S712516


S412507

Perforations,
Engineered to Perform


Schepper's perforated metal panels combine design flexibility, precision and acoustic functionality. Available in round, square and slot patterns, they can also be customised to suit specific design requirements, with each perforation defined by precise hole sizes, spacing and open areas.

Perforation patterns can be further customised through variations in hole geometry, diameter, spacing and open area to meet specific architectural and functional requirements.

Manufactured through precision CNC punching and laser cutting, the panels are available in materials such as aluminium and galvanised steel, with surface finishes tailored to project requirements.


With non-woven cloth (NWC) and glass wool options available, the panels support sound absorption. Acoustic performance can be tailored through different backing materials and thicknesses to achieve the required Noise Reduction Coefficient (NRC) values.

Suitable for ceilings, façades, partitions, screens and other architectural elements, perforated panels bring together visual expression, acoustic performance and functional versatility.




Perforation: Round
Straight 90°

0.7 mm




C9-075

Hole: Ø0.7 mm
Open Area: 5%




C9-0710

Hole: Ø0.7 mm
Open Area: 10%



C9-0712


Hole: Ø0.7 mm
Open Area: 12.5%



C9-0716


Hole: Ø0.7 mm
Open Area: 16%

0.9 mm




C9-095

Hole: Ø0.9 mm
Open Area: 5%




C9-0910

Hole: Ø0.9 mm
Open Area: 10%



C9-0912


Hole: Ø0.9 mm
Open Area: 12.5%



C9-0916


Hole: Ø0.9 mm
Open Area: 16%

1.2 mm




C9-1_25

Hole: Ø1.2 mm
Open Area: 5%




C9-1_210

Hole: Ø1.2 mm
Open Area: 10%



C9-1_212

Hole: Ø1.2 mm
Open Area: 12.5%



C9-1_216


Hole: Ø1.2 mm
Open Area: 16%

And many more...

Note - all measurements are in mm.


Perforation: Round
Staggered 45°

0.7 mm




C4-075

Hole: Ø0.7 mm
Open Area: 5%




C4-0710

Hole: Ø0.7 mm
Open Area: 10%



C4-0712


Hole: Ø0.7 mm
Open Area: 12.5%



C4-0716


Hole: Ø0.7 mm
Open Area: 16%

0.9 mm




C4-095

Hole: Ø0.9 mm
Open Area: 5%




C4-0910

Hole: Ø0.9 mm
Open Area: 10%



C4-0912


Hole: Ø0.9 mm
Open Area: 12.5%



C4-0916


Hole: Ø0.9 mm
Open Area: 16%

1.2 mm




C4-1_25

Hole: Ø1.2 mm
Open Area: 5%




C4-1_210

Hole: Ø1.2 mm
Open Area: 10%



C4-1_212

Hole: Ø1.2 mm
Open Area: 12.5%




C4-1_216

Hole: Ø1.2 mm
Open Area: 16%

And many more...


Perforation: Round
Staggered 60°

0.7 mm




C6-075

Hole: Ø0.7 mm
Open Area: 5%




C6-0710

Hole: Ø0.7 mm
Open Area: 10%



C6-0712


Hole: Ø0.7 mm
Open Area: 12.5%



C6-0716


Hole: Ø0.7 mm
Open Area: 16%

0.9 mm




C6-095

Hole: Ø0.9 mm
Open Area: 5%




C6-0910

Hole: Ø0.9 mm
Open Area: 10%



C6-0912


Hole: Ø0.9 mm
Open Area: 12.5%



C6-0916


Hole: Ø0.9 mm
Open Area: 16%

1.2 mm




C6-1_25

Hole: Ø1.2 mm
Open Area: 5%




C6-1_210

Hole: Ø1.2 mm
Open Area: 10%



C6-1_212

Hole: Ø1.2 mm
Open Area: 12.5%



C6-1_216


Hole: Ø1.2 mm
Open Area: 16%

And many more...

Note - all measurements are in mm.


Perforation: Square
Straight 90°

3x3 mm




S9-35

Square Size: 3x3 mm
Open Area: 5%




S9-310

Square Size: 3x3 mm
Open Area: 10%



S9-312


Square Size: 3x3 mm
Open Area: 12.5%



S9-316


Square Size: 3x3 mm
Open Area: 16%

4x4 mm




S9-45

Square Size: 4x4 mm
Open Area: 5%




S9-410

Square Size: 4x4 mm
Open Area: 10%



S9-412


Square Size: 4x4 mm
Open Area: 12.5%



S9-416


Square Size: 4x4 mm
Open Area: 16%

5x5 mm




S9-55

Square Size: 5x5 mm
Open Area: 5%




S9-510

Square Size: 5x5 mm
Open Area: 10%



S9-512

Square Size: 5x5 mm
Open Area: 12.5%




S9-516

Square Size: 5x5 mm
Open Area: 16%

And many more...


Perforation: Square
Staggered 45°

3x3 mm




S4-35

Square Size: 3x3 mm
Open Area: 5%




S4-310

Square Size: 3x3 mm
Open Area: 10%



S4-312


Square Size: 3x3 mm
Open Area: 12.5%



S4-316


Square Size: 3x3 mm
Open Area: 16%

4x4 mm




S4-45

Square Size: 4x4 mm
Open Area: 5%




S4-410

Square Size: 4x4 mm
Open Area: 10%



S4-412


Square Size: 4x4 mm
Open Area: 12.5%



S4-416


Square Size: 4x4 mm
Open Area: 16%

5x5 mm




S4-55

Square Size: 5x5 mm
Open Area: 5%




S4-510

Square Size: 5x5 mm
Open Area: 10%



S4-512

Square Size: 5x5 mm
Open Area: 12.5%



S4-516


Square Size: 5x5 mm
Open Area: 16%

And many more...

Note - all measurements are in mm.


Perforation: Square
Staggered 60°

3x3 mm




S6-35

Square Size: 3x3 mm
Open Area: 5%




S6-310

Square Size: 3x3 mm
Open Area: 10%



S6-312


Square Size: 3x3 mm
Open Area: 12.5%



S6-316


Square Size: 3x3 mm
Open Area: 16%

4x4 mm




S6-45

Square Size: 4x4 mm
Open Area: 5%




S6-410

Square Size: 4x4 mm
Open Area: 10%



S6-412


Square Size: 4x4 mm
Open Area: 12.5%



S6-416


Square Size: 4x4 mm
Open Area: 16%

5x5 mm




S6-55

Square Size: 5x5 mm
Open Area: 5%




S6-510

Square Size: 5x5 mm
Open Area: 10%



S6-512

Square Size: 5x5 mm
Open Area: 12.5%




S6-516

Square Size: 5x5 mm
Open Area: 16%

And many more...


Perforation: Slot
Straight 90°

2x10 mm




SL9-2105

Slot Size: 2x10 mm
Open Area: 5%



SL9-21010


Slot Size: 2x10 mm
Open Area: 10%



SL9-21012


Slot Size: 2x10 mm
Open Area: 12.5%

2x14 mm




SL9-2145

Slot Size: 2x14 mm
Open Area: 5%



SL9-21410

Slot Size: 2x14 mm
Open Area: 10%



SL9-21412


Slot Size: 2x14 mm
Open Area: 12.5%

And many more...

Note - all measurements are in mm.


Perforation: Slot
Staggered 45°

2x10 mm




SL4-2105

Slot Size: 2x10 mm
Open Area: 5%



SL4-21010


Slot Size: 2x10 mm
Open Area: 10%



SL4-21012


Slot Size: 2x10 mm
Open Area: 12.5%

2x14 mm




SL4-2145

Slot Size: 2x14 mm
Open Area: 5%



SL4-21410

Slot Size: 2x14 mm
Open Area: 10%




SL4-21412

Slot Size: 2x14 mm
Open Area: 12.5%

And many more...


Perforation: Slot
Staggered 60°

2x10 mm




SL6-2105

Slot Size: 2x10 mm
Open Area: 5%



SL6-21010


Slot Size: 2x10 mm
Open Area: 10%



SL6-21012


Slot Size: 2x10 mm
Open Area: 12.5%

2x14 mm




SL6-2145

Slot Size: 2x14 mm
Open Area: 5%



SL6-21410

Slot Size: 2x14 mm
Open Area: 10%



SL6-21412

Slot Size: 2x14 mm
Open Area: 12.5%

And many more...

Note - all measurements are in mm.

Engineered for **Acoustic Performance**

Acoustics refers to how sound behaves within an enclosed space, including how it is absorbed, reflected and transmitted.


In metal ceiling systems, acoustic performance relates to the ability to absorb sound and reduce reverberation, helping create more comfortable indoor environments.

Perforated metal panels combined with suitable acoustic backing materials help control sound reflections while retaining the functional and aesthetic qualities of metal ceilings.

Acoustic performance can be tailored through varying GSM options of Non-Woven Cloth (NWC) and glass wool thicknesses to achieve the required NRC values.

Schepper's Lay-In Tile acoustic ceiling system combines perforated galvanised steel panels with acoustic backing to support effective sound absorption. The system comprises 2.5 mm circular perforations with 16% open area, a 40 gsm non-woven cloth and 50 mm thick glass wool insulation, installed on a 24 mm Tee grid.

Tested acoustic performance records a Noise Reduction Coefficient (NRC) of 1.00, with sound absorption coefficients varying across frequencies. The demountable lay-in construction allows convenient access to the ceiling plenum while maintaining a clean, uniform ceiling finish.




Acoustic Performance

Frequency (Hz)	Sound Absorption Coefficient (α)	NRC
125	0.19	1.00
250	0.99	
500	1.00	
1000	1.00	
2000	1.00	
4000	0.87	


Suspension Details

Suspension options with their minimum and maximum heights, including minimum height requirements for direct fixing to the slab.


With Support Angle



Min. Distance with Support Angle




Min. Distance with Support Angle & Bullet Fastener




Upto Distance with Support Angle & Bullet Fastener


With Height Adjustable Clip



Carrier Direct with Slab




Min. Distance with Big Clip




Upto Distance with Big Clip

With Threaded Rod




Min. Distance with
Threaded Rod




Upto Distance with
Threaded Rod

With Butterfly Clip



Min. Distance with
Butterfly Clip



Upto Distance with
Butterfly Clip

IMPORTANT INFORMATION & DISCLAIMERS

Copyright & Intellectual Property
© 2026 Schepper. All rights reserved. This brochure and its original text, layouts, illustrations, drawings and other proprietary material are protected by copyright. No part may be copied, reproduced, modified, translated, distributed or used commercially without prior written permission from the copyright owner. Third-party trademarks and credited material remain the property of their respective owners.

Colours & Finish Matching
Colours and finishes shown are indicative only. Actual appearance may vary due to printing, photography, screen settings, lighting, viewing angle and substrate. Colour codes and reference samples guide selection but do not guarantee an exact match across different materials, coating systems or production batches. Final selection should be based on an approved physical sample and agreed colour, gloss and texture tolerances.

Product Variations & Tolerances
Minor variations in dimensions, thickness, profile, perforation alignment, texture, gloss and shade may occur within applicable manufacturing tolerances and approved specifications. Samples represent the general appearance of the product. For visually continuous surfaces, material should preferably be ordered together; subsequent supplies may show batch-related variations.

Specifications & Product Updates
Schepper reserves the right to revise product designs, specifications, dimensions, materials, finishes and availability without prior notice. Illustrations and drawings are indicative unless expressly identified as technical drawings. Dimensions are in millimetres unless otherwise stated. Specifications for confirmed orders shall remain subject to the agreed order documents and approved drawings.

Testing, Performance & Certifications
Test results and performance classifications apply only to the products, specimens and system configurations covered by the relevant reports. Performance may vary with material, thickness, finish, backing, supporting structure and installation conditions. References to standards do not imply that every product or configuration is independently tested or certified. Certification scope and validity are governed by the respective certificates.

Selection & Installation
Product suitability, structural requirements, fixing arrangements and compliance with applicable project requirements must be verified by the responsible project professionals. Installation must follow approved drawings, project specifications and applicable Schepper instructions.

Information, Warranty & Liability
Reasonable care has been taken in preparing this brochure; errors and omissions may nevertheless occur. Confirm current technical information with Schepper before specification or purchase. This brochure provides general information and does not, by itself, constitute a contractual offer or warranty. Supply, warranty and liability are governed by the agreed contract and applicable law. Nothing herein excludes obligations or liability that cannot lawfully be excluded.

SCHEPPER®

1800-309-6007 info@schepper.in www.schepper.in

Office Address:

B1301-1302, Sivanta One,
Opp. Nalli Sarees Showroom, Pritamnagar,
Paldi, Ahmedabad 380007, Gujarat, India.

Regional Office Address:

201, 2nd Floor, Subishi Plaza, Behind
GEM Motors, Gachibowli-Miyapur Road,
Kondapur, Hyderabad-500084, Telangana, India.

Mfg. Unit:

FP 202, B/h Tathastu Party Plot,
Nr. SP Ring Road, Ognaj,
Ahmedabad 380060, Gujarat, India.